



General Notes and Legends

Note:-

- Foundation bolts shall be carried out in the existing concrete floor and adequately leveled. Then, the vertical supporting structure shall be bolted to the foundation, as well as fixed to the existing stone masonry wall by means of lateral bracing.

-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

CAMILLERI & CUSCHIERI
CONSULTING ENGINEERS

Design Center, Level 2, Tower Road, Swatar,
Birkirkara, Malta - BKR 4012

+356 21220431 | +356 79220431
info@camilleriandcuschieri.com
www.camilleriandcuschieri.com

Project Name & Address:

Nature Trust

Xrobb L-Għagin

THIS DRAWING IS CONFIDENTIAL AND IS THE PROPERTY OF CAMILLERI & CUSCHIERI CONSULTING ENGINEERS. IT MUST NOT BE DISCLOSED TO A THIRD PARTY, COPIED OR LENT, WITHOUT THE WRITTEN CONSENT OF CAMILLERI & CUSCHIERI CONSULTING ENGINEERS.

Scale:	Revision No.:	Date:
1:100	00	15.10.20

Job No.:	Drawing No.:
20.032	NT-XG.OTC.01.01

Drawn By:	Checked By:
Warren Abela	

Position:

Ground Floor

Service:

Overhead Travelling Crane Detail

A1

PLEASE DO NOT SCALE FROM THE DRAWING